

## E.S400J1 - Electronic torque screwdriver sets - screwing bits



### **Standards:**

**NF EN ISO 6789, ISO 6789, DIN EN ISO 6789**

### **Description:**

- Accuracy:  $\pm 2\%$  clockwise ( $\pm 3\%$  counter clockwise) between 20% and 100% screwdriver capacity.
- Resolution: 0.1 cN.m.
- Measurement mode: tip or follower.
- 1/4" outlet with auto-locking system for series 1 and series 6 bits.
- Measurement unit: cN.m, in.lb, Kg.cm
- Presetting possible of 9 torque values.
- Memory 250 values with PC USB link.
- Locking keypad (program selection and result log only accessible to the operator).
- Hole in the handle for strapping when working in high places.
- Supplied with 1 AAA-LR03 1.5V battery.
- Supplied with an ISO6789 calibration certificate.
- Screwdriver length 215 mm.
- 6 series 6 bits with 1/4" groove - length 50 mm: slotted head 3 - 4 - 5.5 and Phillips® High Perf® 1 - 2 - 3.
- Supplied in plastic case and foam module, dim. (L.xW.xH.): 570x100x70 mm.
- USB cable E.S404-USB and plugs E.S404-KIT set available as spares.

|  | Length L [mm] | Height H [mm] | Length [mm] | Weight [Kg] | Capacity [Nm] |
|--|---------------|---------------|-------------|-------------|---------------|
| <b>E.S404J1</b>  | 570.0         | 70.0          | 100.0       | 1.2         | 0.4 - 4       |