


ATWH - PROTWIST® screwdrivers for slotted head screws - POWER series




Standards:

NF ISO 2380-1, NF ISO 2380-2,
ISO 2380-1, ISO 2380-2, DIN ISO
2380-1, DIN ISO 2380-2, ASME
B107.600

Description:

- Hexagonal blade with shoulder to take a wrench.
- Extra-long shank up to 250 mm for difficult and remote access.
- Inline Hardening Process – +50% Tip Life and +100% Bar Strength.
- Handle Material - Softer for more Comfort and still Chemical Resistant.
- Blade " tri-coating " treatment (Zinc-Nickel-Chromium) - 4x Corrosion Resistance.
- Handle 'Channel' - +10% Torque.
- Laser Marking - gives virtually Permanent Marking.
- CNC tip machining - gives better Screw Fit increasing Torque Transfer and Reducing Wear.

	A [mm]	Diameter [mm]	Diameter D1 [mm]	Length L1 [mm]	Length L [mm]	Length L2 [mm]	Thickness E [mm]	Width [mm]	Weight [g]
ATWH12X200	12.0	40.0	10.0	200.0	325.0	125.0	2.0	12.0	350.0
ATWH14X250	14.0	40.0	12.0	250.0	375.0	125.0	2.5	14.0	450.0
ATWH5.5X125	5.5	30.0	5.0	125.0	234.0	109.0	1.0	5.5	90.0
ATWH5.5X125PB	5.5	30.0	5.0	125.0	234.0	109.0	1.0	5.5	90.0
ATWH6.5X150	6.5	36.0	6.0	150.0	270.0	120.0	1.2	6.5	135.0
ATWH6.5X150PB	6.5	36.0	6.0	150.0	270.0	120.0	1.2	6.5	135.0