

AN - Destornilladores PROTWIST® para tornillos ranurados - hoja fresada



Description:

- Laser Marking - gives virtually Permanent Marking.[es]
- Extra-long shank up to 300 mm for difficult and remote access.[es]
- Inline Hardening Process – +100% Tip Life and +100% Bar Strength. [es]
- Round shank for access in holes.[es]
- Handle Material - Softer for more Comfort and still Chemical Resistant.[es]
- CNC tip machining - gives better Screw Fit increasing Torque Transfer and Reducing Wear.[es]
- Handle 'Channel' - +10% Torque.[es]
- Blade " tri-coating " treatment (Zinc-Nickel-Chromium) - 4x Corrosion Resistance.[es]

	a [mm]	A [mm]	A [mm]	Diámetro [mm]	Diámetro D1 [mm]	Longitud L1 [mm]	Longitud [mm]	Longitud L2 [mm]	Grosor [mm]	Anchura [mm]	Peso [g]
AT2.5X50	2.5	2.5		19.0	2.5	50.0	144.0	94.0	0.4	2.5	20.0
AT2.5X75	2.5	2.5		19.0	2.5	75.0	169.0	94.0	0.4	2.5	21.0
AT2.5X75PB		2.5		19.0	2.5	75.0	169.0	94.0	0.4	2.5	21.0
AT2X75	2.0	2.0		19.0	2.0	75.0	169.0	94.0	0.4	2.0	18.0
AT3.5X100	3.5	3.5		25.0	3.5	100.0	203.0	103.0	0.6	3.5	43.0
AT3.5X100PB		3.5		25.0	3.5	100.0	203.0	103.0	0.6	3.5	43.0
AT3.5X250	3.5	3.5		25.0	3.5	250.0	353.0	103.0	0.6	3.5	55.0
AT3.5X75	3.5	3.5		25.0	3.5	75.0	178.0	103.0	0.6	3.5	41.0
AT3.5X75PB		3.5		25.0	3.5	75.0	178.0	103.0	0.6	3.5	41.0
AT3X100	3.0	3.0		25.0	3.0	100.0	203.0	94.0	0.5	3.0	33.0
AT3X75	3.0	3.0		19.0	3.0	75.0	178.0	94.0	0.5	3.0	32.0
AT4X100	4.0	4.0		25.0	4.0	100.0	209.0	103.0	0.8	4.0	47.0
AT4X100PB		4.0		25.0	4.0	100.0	209.0	103.0	0.8	4.0	47.0
AT4X150	4.0	4.0		25.0	4.0	150.0	259.0	103.0	0.8	4.0	52.0
AT4X200	4.0	4.0		25.0	4.0	200.0	309.0	103.0	0.8	4.0	57.0
AT4X300	4.0	4.0		25.0	4.0	300.0	409.0	103.0	0.8	4.0	120.0
AT5.5X100	5.5	5.5		30.0	3.5	100.0	209.0	109.0	1.0	5.5	82.0
AT5.5X100PB		5.5		30.0	3.5	100.0	209.0	109.0	1.0	5.5	82.0
AT5.5X125	5.5	5.5		30.0	5.5	125.0	234.0	109.0	1.0	5.5	87.0
AT5.5X150	5.5	5.5		30.0	5.5	150.0	259.0	109.0	1.0	5.5	91.0
AT5.5X150PB		5.5		30.0	5.5	150.0	259.0	109.0	1.0	5.5	91.0
AT5.5X200	5.5	5.5		30.0	5.5	200.0	309.0	109.0	1.0	5.5	105.0
AT5.5X300	5.5	5.5		30.0	5.5	300.0	409.0	109.0	1.0	5.5	130.0
AT6.5X125	6.5	6.5		36.0	6.5	125.0	245.0	120.0	1.2	6.5	132.0
AT6.5X150	6.5	6.5		36.0	6.5	150.0	270.0	120.0	1.2	6.5	140.0
AT6.5X150PB		6.5		36.0	6.5	150.0	270.0	120.0	1.2	6.5	140.0
AT6.5X200	6.5	6.5		36.0	6.5	200.0	320.0	120.0	1.2	6.5	153.0

AT6.5X300	6.5	6.5	36.0	6.5	300.0	420.0	120.0	1.2	6.5	180.0
------------------	-----	-----	------	-----	-------	-------	-------	-----	-----	-------