

## 467B - Metric ratchet combination wrenches




### Standards:

NF ISO 1711-1, NF ISO 691, ISO 1711-1, ISO 691, DIN ISO 1711-1, DIN ISO 691

### Description:

- Ultra-Grip ratchet wrenches: retaining pin on the ring + securing notch on the open end. Does not slip on the nuts, optimum safety.
- Compact ratchet mechanism reversing by lever. Better accessibility.
- 5° increments (7.5° for size 6 mm; 6° for 7, 8 and 9 mm sizes). Enhanced productivity.
- Ring and open end tilted at 15°.
- Metric sizes: 6 to 41 mm
- Satin chrome finish.

	A [mm]	A [in]	Length L [mm]	Thickness E [mm]	Thickness E1 [mm]	Thickness E2 [mm]	Head Height C [mm]	Head Width B [mm]	Head Width B1 [mm]	Weight [Kg]
<b>467B.10</b>	10.0		158.0	5.1	7.3	3.4	10.4	22.7	20.2	0.049
<b>467B.10PB</b>	10.0		158.0	5.1	7.3	3.4	10.4	22.7	20.2	0.049
<b>467B.11</b>	11.0		165.0	5.2	7.7	3.5	10.6	23.7	22.0	0.058
<b>467B.11PB</b>	11.0		165.0	5.2	7.7	3.5	10.6	23.7	22.0	0.058
<b>467B.12</b>	12.0		171.0	5.4	8.2	3.8	11.3	26.8	23.2	0.069
<b>467B.12PB</b>	12.0		171.0	5.4	8.2	3.8	11.3	26.8	23.2	0.069
<b>467B.13</b>	13.0		178.0	5.7	8.6	4.3	12.2	28.4	25.3	0.086
<b>467B.13PB</b>	13.0		178.0	5.7	8.6	4.3	12.2	28.4	25.3	0.086
<b>467B.14</b>	14.0		190.0	5.9	9.0	4.3	13.0	30.8	27.0	0.1
<b>467B.14PB</b>	14.0		190.0	5.9	9.0	4.3	13.0	30.8	27.0	0.1
<b>467B.15</b>	15.0		199.0	6.1	9.4	4.7	14.0	32.3	28.3	0.115
<b>467B.15PB</b>	15.0		199.0	6.1	9.4	4.7	14.0	32.3	28.3	0.115
<b>467B.16</b>	16.0		208.0	6.6	9.9	5.3	14.1	34.9	30.0	0.138
<b>467B.16PB</b>	16.0		208.0	6.6	9.9	5.3	14.1	34.9	30.0	0.138
<b>467B.17</b>	17.0		225.0	6.6	10.3	5.4	15.4	36.8	31.7	0.162
<b>467B.17PB</b>	17.0		225.0	6.6	10.3	5.4	15.4	36.8	31.7	0.162
<b>467B.18</b>	18.0		236.0	7.4	10.7	5.8	15.6	38.4	32.8	0.183
<b>467B.18PB</b>	18.0		236.0	7.4	10.7	5.8	15.6	38.4	32.8	0.183
<b>467B.19</b>	19.0		247.0	7.4	11.2	6.0	16.0	41.2	33.9	0.212
<b>467B.19PB</b>	19.0		247.0	7.4	11.2	6.0	16.0	41.2	33.9	0.212
<b>467B.21</b>	21.0		287.0	8.6	13.0	6.3	18.0	46.9	39.7	0.314
<b>467B.22</b>	22.0		287.0	8.6	13.0	6.3	18.0	46.9	39.7	0.314
<b>467B.22PB</b>	22.0		287.0	8.6	13.0	6.3	18.0	46.9	39.7	0.314
<b>467B.24</b>	24.0		320.0	8.9	14.5	6.7	19.5	51.0	46.0	0.414
<b>467B.24PB</b>	24.0		320.0	8.9	14.5	6.7	19.5	51.0	46.0	0.414

<b>467B.27</b>	27.0		356.0	9.8	15.5	7.1	21.0	57.9	52.0	0.567
<b>467B.30</b>	30.0		400.0	10.5	17.0	8.3	24.2	64.9	58.0	0.794
<b>467B.32</b>	32.0		422.0	11.0	17.5	8.5	26.0	67.9	62.2	0.951
<b>467B.34</b>	34.0		455.0	11.0	17.5	8.7	27.0	72.0	62.2	1.026
<b>467B.36</b>	36.0		487.0	13.0	18.0	10.5	30.0	79.9	66.0	1.343
<b>467B.38</b>	38.0		487.0	13.0	18.0	10.5	30.0	79.9	66.0	1.343
<b>467B.41</b>	41.0		565.0	14.0	19.5	12.5	31.3	84.7	72.0	1.871
<b>467B.6</b>	6.0		128.0	4.0	6.3	2.7	6.5	14.1	14.1	0.02
<b>467B.6PB</b>	6.0		128.0	4.0	6.3	2.7	6.5	14.1	14.1	0.02
<b>467B.7</b>	7.0		140.0	4.6	6.5	3.1	8.2	18.6	16.8	0.034
<b>467B.7PB</b>	7.0		140.0	4.6	6.5	3.1	8.2	18.6	16.8	0.034
<b>467B.8</b>	8.0		140.0	4.6	6.5	3.1	8.2	18.6	16.8	0.034
<b>467B.8PB</b>	8.0		140.0	4.6	6.5	3.1	8.2	18.6	16.8	0.034
<b>467B.9</b>	9.0		149.0	4.6	6.9	3.2	9.0	21.0	18.6	0.04
<b>467B.9PB</b>	9.0		149.0	4.6	6.9	3.2	9.0	21.0	18.6	0.04