

AWH.CK - PROTWIST® Wkrętaki PROTWIST® SHOCK do śrub z rowkiem - seria do pobijania



Description:

- Laser Marking - gives virtually Permanent Marking.[pl]
- Impact Zone with Steel Strike - hexagonal blade with 73MO steel.[pl]
- Handle Material - Softer for more Comfort and still Chemical Resistant.[pl]
- Inline Hardening Process – +100% Tip Life and +100% Bar Strength. [pl]
- Golden electroplated Tip - 4x Corrosion Resistance.[pl]
- Hexagonal blade with shoulder to take a wrench.[pl]
- Handle 'Channel' - +10% Torque.[pl]
- Extra-long blade for use in confined spaces.[pl]
- CNC tip machining - gives better Screw Fit increasing Torque Transfer and Reducing Wear.[pl]

	a [m m]	Średni ca [mm] [mm]	Średni ca D1 [mm]	Długo ść L1 [mm]	Długo ść [mm]	Długo ść [mm]	Wag a [g]	Średni ca D2 [mm]	Grubo ść [mm]
ATWH10X175CK	10.0	40.0	7.0	175.0	300.0	125.0	195.0		
ATWH12X200CK	12.0	40.0	1.0	200.0	325.0	125.0	292.0		
ATWH14X250CK	14.0	40.0	10.0	250.0	375.0	125.0	322.0	16.0	2.5
ATWH5.5X125CK	5.5	25.0	4.0	100.0	204.0	104.0	57.0	8.0	1.0
ATWH5.5X125CKPB		25.0	4.0	100.0	204.0	104.0	57.0	8.0	1.0
ATWH6.5X150CK	6.5	30.0	5.0	125.0	235.0	110.0	88.0	10.0	1.2
ATWH6.5X150CKPB		30.0	5.0	125.0	235.0	110.0	88.0	10.0	1.2
ATWH8X175CK	8.0	36.0	6.0	150.0	270.0	120.0	147.0		