

## ATD.VE - PROTWIST® 1,000 Volt insulated screwdrivers for Pozidriv® head screws




### Standards:

NF ISO 8764-1, NF ISO 8764-2, NF EN 60900, ISO 8764-1, ISO 8764-2, EN 60900, DIN ISO 8764-1, DIN ISO 8764-2, DIN EN 60900, ASME B107.600

### Description:

- For your safety, each screwdriver is tested individually at 10,000 volts for 10 seconds, at the end of the manufacturing cycle.
- 1,000 Volt sheathed round blade.
- Bi-material grip resists to impacts, abrasion, and chemicals.

	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	Length L2 [mm]	Length L3 [mm]	Thickness E [mm]	Pozitiv Tip Number ["]	Weight [g]
<b>ATD0X75VE</b>	25.0	3.0	179.0	75.0	104.0	18.0	3.0	PZ0	46.0
<b>ATD1X100VE</b>	30.0	4.5	209.0	100.0	109.0	18.0	4.5	PZ1	77.0
<b>ATD1X100VEPB</b>	30.0	4.5	209.0	100.0	109.0	18.0	4.5	PZ1	77.0
<b>ATD2X125VE</b>	36.0	6.0	245.0	125.0	120.0	18.0	6.0	PZ2	127.0
<b>ATD2X125VEPB</b>	36.0	6.0	245.0	125.0	120.0	18.0	6.0	PZ2	127.0
<b>ATD3X150VE</b>	40.0	8.0	275.0	150.0	125.0	18.0	8.0	PZ3	195.0
<b>ATD3X150VEPB</b>	40.0	8.0	275.0	150.0	125.0	18.0	8.0	PZ3	195.0