


AN - PROTWIST® screwdrivers for Phillips® screws - round blades



Description:

- Blade " tri-coating " treatment (Zinc-Nickel-Chromium) - 4x Corrosion Resistance.[nl]
- Inline Hardening Process – +50% Tip Life and +100% Bar Strength. [nl]
- Extra-long blade up to 400 mm for difficult and remote access.[nl]
- CNC tip machining - gives better Screw Fit increasing Torque Transfer and Reducing Wear.[nl]
- Handle Material - Softer for more Comfort and still Chemical Resistant.[nl]
- Laser Marking - gives virtually Permanent Marking.[nl]
- Handle 'Channel' - +10% Torque.[nl]

	Diameter [mm]	Diameter D1 [mm]	Lengte L1 [mm]	Lengte [mm]	Lengte [mm]	Gewicht [g]	Phillips Tip Aantal ["]
ATP0X75	25.0	3.0	75.0	178.0	103.0	45.0	PH0
ATP0X75PB	25.0	3.0	75.0	178.0	103.0	45.0	PH0
ATP1X100	30.0	4.5	100.0	209.0	109.0	76.0	PH1
ATP1X100PB	30.0	4.5	100.0	209.0	109.0	76.0	PH1
ATP1X250	30.0	4.5	250.0	359.0	109.0	99.0	PH1
ATP1X75	30.0	4.5	75.0	184.0	109.0	73.0	PH1
ATP2X100	36.0	6.0	100.0	220.0	120.0	120.0	PH2
ATP2X125	36.0	6.0	125.0	245.0	120.0	126.0	PH2
ATP2X125PB	36.0	6.0	125.0	245.0	120.0	126.0	PH2
ATP2X250	36.0	6.0	250.0	370.0	120.0	153.0	PH2
ATP2X250PB	36.0	6.0	250.0	370.0	120.0	153.0	PH2
ATP2X400	36.0	6.0	400.0	520.0	120.0	186.0	PH2
ATP3X150	40.0	8.0	150.0	275.0	125.0	194.0	PH3
ATP3X150PB	40.0	8.0	150.0	275.0	125.0	194.0	PH3
ATP4X200	40.0	10.0	200.0	325.0	125.0	277.0	PH4