


## 440 - Metrische ringsteeksleutels



### Description:

- Ring head: - Ring clearance (E dimension) designed for better access to serial-mounted or embedded screws. - OGV® profile 12-point ring for powerful tightening while protecting the nut. Suffix H = 6 sided ring. - Ring head with 15° angle.[nl]
- Open end head: - Open end with 15° angle. - Open end head-handle geometry optimized for increased accessibility.[nl]
- Standard wrench for all common applications. [nl]
- High mechanical performance combined with compact design complying with aeronautical standards.[nl]
- Metric dimensions: 4 to 41 mm.[nl]
- Satin chrome finish.[nl]

	a [mm]	A [mm]	Lengte [mm]	Dikte [mm]	Dikte E1 [mm]	Dikte E2 [mm]	Hoofd Breedte B [mm]	Hoofd Breedte B1 [mm]	Gewicht [kg]
<b>440.10</b>	10.0	10.0	145.0	4.2	7.6	5.2	23.0	15.0	0.04
<b>440.10PB</b>		10.0	145.0	4.2	7.6	5.2	23.0	15.0	0.04
<b>440.11</b>	11.0	11.0	155.0	4.6	8.1	5.5	24.5	16.9	0.05
<b>440.11PB</b>		11.0	155.0	4.6	8.1	5.5	24.5	16.9	0.05
<b>440.12</b>	12.0	12.0	162.0	4.4	8.4	5.8	27.0	18.0	0.06
<b>440.12PB</b>		12.0	162.0	4.4	8.4	5.8	27.0	18.0	0.06
<b>440.13</b>	13.0	13.0	170.0	4.8	8.6	6.1	28.7	19.3	0.07
<b>440.13PB</b>		13.0	170.0	4.8	8.6	6.1	28.7	19.3	0.07
<b>440.14</b>	14.0	14.0	180.0	5.7	9.5	6.4	31.0	21.1	0.085
<b>440.14PB</b>		14.0	180.0	5.7	9.5	6.4	31.0	21.1	0.085
<b>440.15</b>	15.0	15.0	185.0	5.9	10.0	6.8	32.6	22.2	0.095
<b>440.15PB</b>		15.0	185.0	5.9	10.0	6.8	32.6	22.2	0.095
<b>440.16</b>	16.0	16.0	195.0	6.4	10.5	7.3	35.6	23.9	0.115
<b>440.16PB</b>		16.0	195.0	6.4	10.5	7.3	35.6	23.9	0.115
<b>440.17</b>	17.0	17.0	202.0	6.5	10.9	7.6	37.0	25.3	0.13
<b>440.17PB</b>		17.0	202.0	6.5	10.9	7.6	37.0	25.3	0.13
<b>440.18</b>	18.0	18.0	208.0	7.2	11.4	8.1	38.7	26.0	0.15
<b>440.18PB</b>		18.0	208.0	7.2	11.4	8.1	38.7	26.0	0.15
<b>440.19</b>	19.0	19.0	216.0	7.2	11.9	8.3	41.2	27.8	0.17
<b>440.19PB</b>		19.0	216.0	7.2	11.9	8.3	41.2	27.8	0.17
<b>440.20</b>	20	20.0	224.0	6.3	12.3	8.6	43.1	29.5	0.185
<b>440.21</b>	21.0	21.0	233.0	7.8	12.8	8.8	45.4	30.9	0.205
<b>440.21PB</b>		21.0	233.0	7.8	12.8	8.8	45.4	30.9	0.205
<b>440.22</b>	22.0	22.0	248.0	8.3	13.3	9.0	46.9	32.3	0.23
<b>440.22PB</b>		22.0	248.0	8.3	13.3	9.0	46.9	32.3	0.23
<b>440.23</b>	23	23.0	257.0	8.7	13.8	9.3	49.0	33.6	0.255
<b>440.23PB</b>		23.0	257.0	8.7	13.8	9.3	49.0	33.6	0.255

<b>440.24</b>	24.0	24.0	267.0	8.9	14.2	9.7	51.0	35.0	0.29
<b>440.24PB</b>		24.0	267.0	8.9	14.2	9.7	51.0	35.0	0.29
<b>440.25</b>	25	25.0	274.0	9.4	14.7	9.9	53.0	36.4	0.315
<b>440.25PB</b>		25.0	274.0	9.4	14.7	9.9	53.0	36.4	0.315
<b>440.26</b>	26.0	26.0	285.0	9.8	15.1	10.1	55.5	37.8	0.345
<b>440.26PB</b>		26.0	285.0	9.8	15.1	10.1	55.5	37.8	0.345
<b>440.27</b>	27.0	27.0	295.0	8.9	15.6	10.4	58.0	39.2	0.375
<b>440.27PB</b>		27.0	295.0	8.9	15.6	10.4	58.0	39.2	0.375
<b>440.28</b>	28.0	28.0	305.0	10.6	16.1	10.7	60.7	40.6	0.415
<b>440.28PB</b>		28.0	305.0	10.6	16.1	10.7	60.7	40.6	0.415
<b>440.29</b>	29.0	29.0	320.0	10.8	16.6	11.2	63.0	42.0	0.475
<b>440.29PB</b>		29.0	320.0	10.8	16.6	11.2	63.0	42.0	0.475
<b>440.30</b>	30.0	30.0	340.0	11.2	17.1	11.5	65.0	43.5	0.53
<b>440.30PB</b>		30.0	340.0	11.2	17.1	11.5	65.0	43.5	0.53
<b>440.32</b>	32.0	32.0	355.0	11.5	18.0	12.5	68.0	46.1	0.64
<b>440.33</b>	33	33.0	380.0	11.8	18.5	12.8	69.8	47.0	0.715
<b>440.34</b>	34	34.0	390.0	12.8	19.0	13.0	72.0	48.9	0.745
<b>440.35</b>	35	35.0	430.0	12.8	19.5	13.5	74.3	51.0	0.89
<b>440.36</b>	36	36.0	440.0	13.2	20.0	14.0	76.0	53.0	0.945
<b>440.38</b>	38	38.0	450.0	14.1	22.0	15.2	80.0	56.0	1.1
<b>440.41</b>	41	41.0	460.0	14.7	23.0	16.0	85.0	58.3	1.3
<b>440.4H</b>	4	4.0	106.0	2.1	3.5	3.0	10.0	7.8	0.01
<b>440.5.5H</b>		5.5	115.0	3.1	6.0	3.8	13.3	9.2	0.015
<b>440.5H</b>	5	5.0	115.0	3.1	6.0	3.6	13.3	9.2	0.016
<b>440.6</b>	6	6.0	115.0	3.1	6.0	3.8	14.1	10.0	0.02
<b>440.6PB</b>		6.0	115.0	3.1	6.0	3.8	14.1	10.0	0.02
<b>440.7</b>	7.0	7.0	122.0	3.4	6.2	3.9	17.2	11.2	0.02
<b>440.7PB</b>		7.0	122.0	3.4	6.2	3.9	17.2	11.2	0.02
<b>440.8</b>	8.0	8.0	133.0	3.5	6.7	4.7	19.2	12.8	0.03
<b>440.8PB</b>		8.0	133.0	3.5	6.7	4.7	19.2	12.8	0.03
<b>440.9</b>	9	9.0	138.0	3.9	7.1	4.7	21.2	14.2	0.035
<b>440.9PB</b>		9.0	138.0	3.9	7.1	4.7	21.2	14.2	0.035