

## 192A.CPE High-performance diagonal cutters



### **Standards:**

**NF ISO 5749, ISO 5749, DIN ISO 5749, ASME B107.500**

### **Description:**

- New head design to increase durability and cutting capacity
- Cutting edges designed to cleanly cut all types of wire: soft wires and modern materials to a maximum piano wire specification of: - 192A.16CPE : 2.0mm 210 kg/mm<sup>2</sup> - 192A.18CPE : 2.2mm 205 kg/mm<sup>2</sup> - 192A.20CPE : 2.5mm 200 kg/mm<sup>2</sup>
- High Mechanical advantage due to off-set rivet and cutting edge geometry reducing effort.
- High durability Carbon alloy steel, with induction hardened cutting edges.
- Bi-Material ergonomic grips resistant to chemical agents featuring: - Return spring - Tether ready point (Tether point adds 10mm to nominal length)
- Chrome finish for corrosion resistance

	Diameter D Maxi [mm]	Length L [mm]	Thickness E [mm]	Head Height C [mm]	Head Width B [mm]	Head Width B1 [mm]	Weight [Kg]
<b>192A.16CPE</b>	2.0	160.0	10.0	180.0	24.0	15.0	0.2
<b>192A.16CPEPB</b>	2.0	160.0	10.0	180.0	24.0	15.0	0.2
<b>192A.18CPE</b>	2.2	180.0	11.0	20.0	26.0	18.0	0.26
<b>192A.18CPEPB</b>	2.2	180.0	11.0	20.0	26.0	18.0	0.26
<b>192A.20CPE</b>	2.5	200.0	11.5	22.0	28.0	22.0	0.32