

J - 3/8" inch 12-point sockets




Standards:

ASME B107.1

Description:

- OGV® profile: more powerful tightening, preserves fasteners.
- Available as rack sets (Ref J.40U).
- Finish: bright chrome.

	A [mm]	A [in]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	12-Point [mm]	Weight [g]
J.1/2		1/2"	17.5	18.1	30.0	10.4	12.0	36.0
J.1/4		1/4"	17.5	10.0	27.0	6.0	12.0	24.0
J.11/16		11/16"	21.0	24.0	33.0	13.0	12.0	74.0
J.13/16		13/16"	23.0	28.0	33.0	16.0	12.0	79.0
J.15/16		15/16"	26.3	31.3	33.0	16.5	12.0	136.0
J.1P	1.0		28.3	33.3	33.0	16.5	12.0	156.0
J.3/4		3/4"	22.7	26.0	33.0	14.0	12.0	76.0
J.3/8		3/8"	17.6	14.1	27.0	7.5	12.0	26.0
J.5/16		5/16"	17.5	11.9	27.0	6.5	12.0	25.0
J.5/8		5/8"	20.0	22.0	30.0	12.0	12.0	46.0
J.7/16		7/16"	17.5	16.0	27.0	9.0	12.0	27.0
J.7/8		7/8"	24.7	29.7	33.0	16.5	12.0	104.0
J.9/16		9/16"	17.7	19.5	30.0	10.5	12.0	34.0