

## J - 3/8" metric 12-point sockets




### **Standards:**

NF ISO 2725-1, NF ISO 1711-1,  
ISO 2725-1, ISO 1711-1, DIN  
3124, ASME B107.5

### **Description:**

- OGV® profile: more powerful tightening, preserves fasteners.
- Finish: bright chrome.

	A [mm]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	12-Point [mm]	Weight [g]
J.10	10.0	17.6	14.7	27.0	7.8	12.0	26.0
J.11	11.0	17.6	16.0	27.0	9.0	12.0	27.0
J.12	12.0	17.6	17.2	27.0	9.5	12.0	26.0
J.13	13.0	17.5	18.3	30.0	10.4	12.0	36.0
J.14	14.0	17.7	19.5	30.0	10.5	12.0	34.0
J.15	15.0	19.0	20.8	30.0	12.0	12.0	38.0
J.16	16.0	20.0	22.0	30.0	12.0	12.0	45.0
J.17	17.0	21.7	23.4	30.0	13.0	12.0	52.0
J.18	18.0	21.7	24.7	33.0	13.0	12.0	69.0
J.19	19.0	22.7	26.0	33.0	14.0	12.0	62.0
J.20	20.0	22.2	27.2	33.0	15.0	12.0	70.0
J.21	21.0	23.5	28.5	33.0	16.0	12.0	75.0
J.22	22.0	24.7	29.7	33.0	16.5	12.0	80.0
J.23	23.0	26.0	31.0	33.0	16.5	12.0	90.0
J.24	24.0	26.3	31.3	33.0	16.5	12.0	86.0
J.7	7.0	17.6	11.0	27.0	6.0	12.0	24.0
J.8	8.0	17.6	12.2	27.0	6.5	12.0	25.0
J.9	9.0	17.6	13.5	27.0	6.7	12.0	25.0