

## J.LA - 3/8" inch 12-point sockets




**Standards:**

**ASME B107.1**

**Description:**

- OGV® profile: more powerful tightening, preserves fasteners.
- Long-reach sockets for long recess or thread access.
- Finish: bright chrome.

	A [in]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	12-Point [mm]	Weight [g]
<b>J.1/2LA</b>	1/2"	18.2	18.2	44.7	7.4	12.0	50.0
<b>J.1/4LA</b>	1/4"	17.5	10.6	44.7	4.0	12.0	36.0
<b>J.11/16LA</b>	11/16"	23.8	23.8	63.8	10.2	12.0	113.0
<b>J.13/16LA</b>	13/16"	27.0	27.0	63.8	12.3	12.0	140.0
<b>J.15/16LA</b>	15/16"	31.8	31.8	63.8	12.7	12.0	185.0
<b>J.1PLA</b>							
<b>J.3/4LA</b>	3/4"	25.3	25.3	63.8	11.8	12.0	127.0
<b>J.3/8LA</b>	3/8"	17.5	14.3	44.7	4.7	12.0	41.0
<b>J.5/16LA</b>	5/16"	17.5	12.4	44.7	4.3	12.0	36.0
<b>J.5/8LA</b>	5/8"	22.3	22.3	63.8	10.2	12.0	104.0
<b>J.7/16LA</b>	7/16"	17.5	16.2	44.7	6.2	12.0	45.0
<b>J.7/8LA</b>	7/8"	30.2	30.2	63.8	12.7	12.0	181.0
<b>J.9/16LA</b>	9/16"	20.5	20.5	48.0	9.0	12.0	72.0