

## J.LA - 3/8" long-reach metric 12-point sockets




### **Standards:**

**NF ISO 2725-1, NF ISO 1711-1,  
ISO 2725-1, ISO 1711-1, DIN  
3124, ASME B107.5**

### **Description:**

- OGV® profile: more powerful tightening, preserves fasteners.
- Long-reach sockets for long recess or thread access.
- Available as rack sets (Ref JL.40U).
- Finish: bright chrome.

|  | A [mm] | Diameter [mm] | Diameter D1 [mm] | Length L [mm] | Length L1 [mm] | 12-Point [mm] | Weight [g] |
|--|--------|---------------|------------------|---------------|----------------|---------------|------------|
| J.10LA   | 10.0   | 17.3          | 14.5             | 55.0          | 9.0            | 12.0          | 50.0       |
| J.11LA   | 11.0   | 17.3          | 16.0             | 55.0          | 10.5           | 12.0          | 53.0       |
| J.12LA   | 12.0   | 17.3          | 16.8             | 55            | 12             |               |            |
| J.13LA   | 13.0   | 17.2          | 18.0             | 55.0          | 12.0           | 12.0          | 54.0       |
| J.14LA   | 14.0   | 17.0          | 20.0             | 55.0          | 15.0           | 12.0          | 60.0       |
| J.15LA   | 15.0   | 18.0          | 21.0             | 55.0          | 15.0           | 12.0          | 75.0       |
| J.16LA   | 16.0   | 20.0          | 22.0             | 60.0          | 15.0           | 12.0          | 85.0       |
| J.17LA   | 17.0   | 20.0          | 23.5             | 60.0          | 15.0           | 12.0          | 102.0      |
| J.18LA   | 18.0   | 22.0          | 24.5             | 60.0          | 18.0           | 12.0          | 109.0      |
| J.19LA   | 19.0   | 23.0          | 25.0             | 60.0          | 18.0           | 12.0          | 110.0      |
| J.21LA   | 21.0   | 24.0          | 27.0             | 60.0          | 18.0           | 12.0          | 123.0      |
| J.22LA   | 22.0   | 26.0          | 29.0             | 60.0          | 21.0           | 12.0          | 150.0      |
| J.24LA   | 24.0   | 30.0          | 31.0             | 60.0          | 21.0           | 12.0          | 176.0      |
| J.7LA  | 7.0    | 17.3          | 10.6             | 55.0          | 6.0            | 12.0          | 44.0       |
| J.8LA  | 8.0    | 17.3          | 12.0             | 55.0          | 7.5            | 12.0          | 46.0       |
| J.9LA  | 9.0    | 17.3          | 13.0             | 55.0          | 7.5            | 12.0          | 47.0       |