

J.HLA - 3/8" long-reach metric 6-point sockets




Standards:

**NF ISO 2725-1, NF ISO 1711-1,
ISO 2725-1, ISO 1711-1, DIN
3124, ASME B107.5**

Description:

- OGV® profile: more powerful tightening, preserves fasteners.
- Long-reach sockets for long recess or thread access.
- Available as rack set Ref JL.40E (7 -- > 15 mm) and Ref RL.41E (16 --> 24 mm).
- Finish: bright chrome.

	A [mm]	Hex Size [mm]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	Weight [g]
J.10HLA	10.0	6.0	17.3	14.5	55.0	9.0	50.0
J.11HLA	11.0	6.0	17.3	16.0	55.0	10.5	53.0
J.12HLA	12.0	6.0	17.2	16.8	55.0	12.0	53.0
J.13HLA	13.0	6.0	17.0	18.0	55.0	12.0	54.0
J.14HLA	14.0	6.0	18.0	20.0	55.0	15.0	60.0
J.15HLA	15.0	6.0	20.0	21.0	60.0	15.0	75.0
J.16HLA	16.0	6.0	20.0	22.0	60.0	15.0	85.0
J.17HLA	17.0	6.0	22.0	23.5	60.0	15.0	102.0
J.18HLA	18.0	6.0	23.0	24.5	60.0	18.0	109.0
J.19HLA	19.0	6.0	24.0	25.0	60.0	18.0	110.0
J.21HLA	21.0	6.0	26.0	27.0	60.0	18.0	123.0
J.22HLA	22.0	6.0	28.0	29.0	60.0	21.0	150.0
J.24HLA	24.0	6.0	30.0	31.0	60.0	24.0	176.0
J.7HLA	7.0	6.0	17.3	10.6	55.0	6.0	44.0
J.8HLA	8.0	6.0	17.3	12.0	55.0	7.5	46.0
J.9HLA	9.0	6.0	17.3	13.0	55.0	7.5	47.0