

K.LA 3/4" long-reach metric 6-point sockets




Standards:

**NF ISO 2725-1, NF ISO 1711-1,
ISO 2725-1, ISO 1711-1, DIN
3124, ASME B107.5**

Description:

- OGV® profile: more powerful tightening, preserves fasteners.
- Secure attachment of plunger lock accessories
- Quick release button.
- Finish: satin chrome.

	A [mm]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	Hex Size [mm]	Weight [g]
K.19LA	19.0	36.0	30.1	90.0	18.0	6.0	339.0
K.21LA	21.0	36.0	32.0	90.0	18.0	6.0	367.0
K.22LA	22.0	36.0	33.4	90.0	21.0	6.0	391.0
K.23LA	23.0	38.0	36.0	90.0	21.0	6.0	461.0
K.24LA	24.0	38.0	36.0	90.0	24.0	6.0	400.0
K.26LA	26.0	36.0	38.9	90.0	24.0	6.0	474.0
K.27LA	27.0	38.0	39.7	90.0	27.0	6.0	480.0
K.29LA	29.0	40.0	42.0	90.0	27.0	6.0	505.0
K.30LA	30.0	40.0	43.2	90.0	30.0	6.0	530.0
K.32LA	32.0	40.0	45.9	90.0	33.0	6.0	540.0
K.33LA	33.0	45.0	48.1	90.0	33.0	6.0	600.0
K.34LA	34.0	45.0	48.4	90.0	33.0	6.0	656.0
K.35LA	35.0	45.0	50.1	90.0	33.0	6.0	707.0
K.36LA	36.0	45.0	51.0	90.0	36.0	6.0	672.0
K.38LA	38.0	45.0	54.3	90.0	36.0	6.0	772.0
K.41LA	41.0	45.0	57.3	90.0	40.0	6.0	778.0
K.42LA	42.0	45.0	59.5	90.0	40.0	6.0	863.0