

K.B 3/4" drive metric 12-point sockets




Standards:

NF ISO 2725-1, NF ISO 1711-1,
ISO 2725-1, ISO 1711-1, DIN
3124, ASME B107.5

Description:

- OGV® profile: more powerful tightening, preserves fasteners.
- Secure attachment of plunger lock accessories
- Quick release button.
- Finish: satin chrome.

	A [mm]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	Weight [g]	Colour □
K.19B	19.0	36.0	30.1	51.0	14.0	207.0	Red 3020
K.21B	21.0	36.0	32.0	51.0	14.0	208.0	Black 9004
K.22B	22.0	36.0	33.4	51.0	14.0	221.0	
K.23B	23.0	36.0	36.0	52.5	14.0	244.0	
K.24B	24.0	36.0	36.0	52.5	16.0	237.0	
K.26B	26.0	36.0	38.9	52.5	16.0	231.0	
K.27B	27.0	36.0	39.7	52.5	18.0	232.0	
K.28B	28.0	36.0	41.0	52.5	18.0	239.0	
K.30B	30.0	36.0	43.2	59.0	20.0	282.0	
K.32B	32.0	36.0	45.9	59.0	22.0	301.0	
K.33B	33.0	36.0	48.1	59.0	22.0	330.0	
K.34B	34.0	36.0	48.4	59.0	24.0	322.0	
K.35B	35.0	36.0	50.1	59.0	24.0	344.0	
K.36B	36.0	36.0	51.0	59.0	24.0	347.0	
K.38B	38.0	40.0	54.3	66.9	27.0	478.0	
K.40B	40.0	40.0	56.0	66.9	27.0	493.0	
K.41B	41.0	40.0	57.3	66.9	27.0	504.0	
K.42B	42.0	40.0	59.5	66.9	27.0	552.0	
K.43B	43.0	40.0	60.7	66.9	28.0	301.0	
K.44B	44.0	40.0	61.9	66.9	28.0	587.0	
K.46B	46.0	40.0	63.5	75.0	30.0	641.0	
K.50B	50.0	40.0	68.5	75.0	33.0	725.0	
K.54B	54.0	45.0	74.0	75.0	36.0	880.0	
K.55B	55.0	45.0	74.7	75.0	36.0	875.0	